



Article number	D-10A	D-15A	D-20A	D-30A
Output Power :	10A Continuous Power 15A Max. Power	15A Continuous Power 20A Max. Power	20A Continuous Power 30A Max. Power	30A Continuous Power 40A Max. Power
Standby Current :	<0.02A	<0.02A	<0.04A	<0.04A
Input Voltage :	DC 20~30V	DC 20~30V	DC 20~30V	DC 20~30V
Output Voltage :	DC 12~13.8V	DC 12~13.8V	DC 12~13.8V	DC 12~13.8V
Efficiency :	>90%	>90%	>90%	>80%
Cooling :	By air convection	Auto Operation Fan	Auto Operation Fan	Auto Operation Fan
Input Polarity Reverse	Diode Protection	Diode Protection	Diode Protection	Diode Protection
Output Polarity Reverse	Circuit Protection	Circuit Protection	Circuit Protection	Circuit Protection
Output Short	Output Short Circuit Protection	Output Short Circuit Protection	Output Short Circuit Protection	Output Short Circuit Protection
Over Heating	Circuit Protection	Circuit Protection	Circuit Protection	Protection Auto Restart After 5 min.
Overload	Circuit Protection	Circuit Protection	Circuit Protection	Circuit Protection
Fuse	10A*1 PC	15A*1 PC	20A*1 PC	25A*1 PC
Dimensions (LxWxd)	70x73x45 mm	71x73x73 mm	120x73x73 mm	180x73x73 mm
Net Weight	0.26 kg	0.33 kg	0.6 kg	0.72 kg